

Victaulic® Strapless Outlet

Style 923



11.05



NPT & BSPT Models



BSPP Model



1.0 PRODUCT DESCRIPTION

Available Sizes

- 4 – 8"/DN100 – DN200 for use on pipe with nominal wall thickness ranging between 0.237 – 0.322"/6.0 – 8.2 mm
- 10"/DN250 and larger for use on pipe with nominal wall thickness ranging between 0.165 – 0.406"/4.2 – 10.3 mm

Maximum Working Pressure

- 300 psi/2068 kPa

Function

- Provides a pipe outlet without the need for a strap or lower housing to wrap around the pipe
- Main body casting has an internal lug that inserts into a hole cut in the pipe and grips against the pipe's inside wall.
- Tightened nut on the main body forces the gasket and containing collar against the pipe's outside surface, creating a rigid joint.

2.0 CERTIFICATION/LISTINGS



EN 10311
CPR (EU)
No. 305/2011



BS EN 10311
CPR (UK)
2019 No. 465

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.



3.0 SPECIFICATIONS – MATERIAL

Housing: Ductile iron conforming to ASTM A536, Grade 65-45-12, painted black. Ductile iron conforming to ASTM A395, Grade 65-45-15, is available upon special request.

Collar: Hot rolled, pickled and oiled steel, conforming to ASTM A569, zinc electroplated to ASTM B633

Bushing: Brass per UNS C37700

Seat/Liner: (specify choice¹)

☐ **Grade “E” EPDM**

EPDM (Green stripe color code). Temperature range –30°F to +230°F/–34°C to +110°C. May be specified for hot water service within the specified temperature range plus a variety of dilute acids, oil-free air and many chemical services.


☐ **Grade “T” Nitrile**

Nitrile (Orange stripe color code). Temperature range –20°F to +180°F/–29°C to +82°C. May be specified for petroleum products, hydrocarbons, air with oil vapors, vegetable and mineral oils within the specified temperature range; not compatible for hot dry air over +140°F/+60°C and water over +150°F/+66°C. NOT COMPATIBLE FOR USE WITH HOT WATER SERVICES OR STEAM SERVICES.

¹ Services listed are General Service Guidelines only. It should be noted that there are services for which these gaskets are not compatible. Reference should always be made to the latest [Victaulic Gasket Selection Guide](#) for specific gasket service guidelines and for a listing of services which are not compatible.

4.0 DIMENSIONS

Style 923 Strapless Outlet



	Size				Dimensions							Weight	
	Nominal		Actual Outside Diameter		Hole Dimensions		Style 923 Dimensions					Approx. (Each) lb kg	
					Hole Saw Size inches mm	Max. Permissible Diameter inches mm	T ³ inches mm	X inches mm	X ₁ inches mm	X ₂ inches mm	Y ⁴ inches mm		
	Run x Branch inches DN	Run x Branch inches mm											
NPT & BSPT Models	4 – 8 DN100 – DN200	1/2 DN15	4.500 – 8.625 114.3 – 219.1	0.840 21.3	1.50 38	1.56 40	2.47 63	3.21 82	–	–	3.09 78	1.9 0.9	
		3/4 DN20		1.050 26.9	1.50 38	1.56 40	2.44 62	3.21 82	–	–	3.09 78	1.6 0.7	
		10 and larger DN250 and larger		1/2 DN15	10.750 and larger 273.0 mm and larger	0.840 21.3	1.50 38	1.56 40	2.47 63	3.21 82	–	–	3.00 76
	3/4 DN20	1.050 26.9	1.50 38	1.56 40		2.44 62	3.21 82	–	–	3.00 76	1.6 0.7		
	BSPP Model	4 - 8 ² DN100 - DN200	1/2 DN15	4.500 - 8.625 114.3 - 219.1	0.840 21.3	1.50 38	1.56 40	2.47 63	–	4.50 114	3.21 82	3.09 78	2.1 1.0
			3/4 DN20		1.050 26.9	1.50 38	1.56 40	2.44 62	–	4.50 114	3.21 82	3.09 78	1.8 0.8
10 and larger ² DN250 and larger			1/2 DN15		10.750 and larger 273.0 mm and larger	0.840 21.3	1.50 38	1.56 40	2.47 63	–	4.50 114	3.21 82	3.00 76
3/4 DN20		1.050 26.9	1.50 38	1.56 40		2.44 62	–	4.50 114	3.21 82	3.00 76	1.8 0.8		

² BSPP outlet, with BSPT male x BSPP female threaded bushing

³ Inside wall of run to end of probe

⁴ Width of collar is as supplied. Width assembled changes due to collar deformation at assembly.

5.0 PERFORMANCE

Style 923 Strapless Outlet

Size				Maximum Working Pressure ⁵⁻⁶ psi kPa	Nominal Wall Thickness Range		
Nominal Run x Branch inches DN		Actual Outside Diameter Run x Branch inches mm			inches mm		
					Minimum	Maximum	
4 – 8 DN100 – DN200	x	½	4.500 – 8.625		0.840	300	0.237 6.0
		DN15	114.3 – 219.1	21.3	2068		
	DN20	x	¾	1.050	300		
			DN20	26.9	2068		
10 and larger DN250 and larger	x	½	10.750 and larger	0.840	300	0.165 4.2	0.406 10.3
		DN15	273.0 mm and larger	21.3	2068		
	DN20	x	¾	1.050	300		
			DN20	26.9	2068		

⁵ Pressure rating is for Style 923 outlet only. Pipe used must also be rated at this pressure or higher.

⁶ BSPP model requires the use of a face seal per ISO 228-1.

NOTES

- Flow area equivalent to ¾"/20 mm pipe. Accepts 7/16"/11 mm diameter pipe.

6.0 NOTIFICATIONS

⚠ WARNING



- Read and understand all instructions before attempting to install any Victaulic products.
- Always verify that the piping system has been completely depressurized and drained immediately prior to installation, removal, adjustment, or maintenance of any Victaulic products.
- Confirm that any equipment, branch lines, or sections of piping that may have been isolated for/during testing or due to valve closures/positioning are identified, depressurized, and drained immediately prior to installation, removal, adjustment, or maintenance of any Victaulic products.
- Wear safety glasses, hard hat, foot protection, and hearing protection.

Failure to follow these instructions could result in death or serious personal injury and property damage.

DUE TO DEFORMATION OF THE COLLAR, THE VICTAULIC STYLE 923 STRAPLESS OUTLET SHALL NOT BE REUSED AFTER INITIAL INSTALLATION.

7.0 REFERENCE MATERIALS

[I-100: Victaulic Field Installation Handbook](#)

User Responsibility for Product Selection and Suitability

Each user bears final responsibility for determining the suitability of Victaulic products for their end-use application, in accordance with industry standards, project specifications, and Victaulic's published performance, maintenance, and safety data, as well as all warnings and installation instructions. Nothing in this or any other document, nor any verbal recommendation, advice, or opinion from any Victaulic employee, shall be deemed to alter, vary, supersede, or waive any provision of Victaulic Company's standard conditions of sale, warranty, installation instructions, or this disclaimer.

Installation

Always refer to and follow the [Victaulic Installation Handbook](#) or installation instructions for the product you are installing. Handbooks are included with each shipment of Victaulic products, providing complete installation and assembly data, and are available in PDF format on our website at [victaulic.com](#).

Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

Intellectual Property Rights

No statement concerning the use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Victaulic or any of its affiliates, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right. The terms "Patented" or "Patent Pending" refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries. Victaulic and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries.

Note

All products bearing a Victaulic trademark are manufactured by Victaulic or to Victaulic specifications. All products are to be installed only in accordance with the applicable Victaulic installation instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.